Faraday Rotator Mirror

Features

- Low Tolerance
- Low Insertion
- Comply with RoHS

Applications

- Telecommunications
- FTTH, CATV, LAN

Single Stage SPECIFICATIONS

PARAMETERS	P Grade	
Operating Wavelength	1310nm, 1480nm or 1550nm	1064nm
Bandwidth	±15nm	±5nm
Insertion Loss (Typical)	≦0.6dB(0.4)	≦3dB(2.6)
Faraday Rotation Angle (Single Pass)	22.5 ° or 45°	45°
Rotation Angle Tolerance over Wavelength and Temperature	±0.5°	±3°
PDL	≦0.05dB	≦0.05dB
Operating Temperature	-5~70 ℃	-5~70 ℃
Storage Temperature	-40~85℃	-40~85℃
Max. Power	300mW	150mW

W S C E ☐ 0 0 ☐ ☐ ☐ ☐ ☐ ☐ 0

Product Type
1=FRM 45°
2=FRM 22.5°

Wavelength
1=1310nm
2=1550nm
3=1480nm
4=1064nm
X=others

Grade
P=P Grade
X=others

Fiber Type
0=0.25mm
1=0.9mm
2=3mm
X=others

Fiber Length
1=1m
2=2m
3=3m
.....
X=others

Dimensions (mm)
0=5.5*34
1=5.5*25.7
2=5.5*35
3=5.5*39
4=98*14*8.5
5=95*12*10
6=4.5*20
X=others

Output Connector
0=None
F=FC/PC
S=SC/PC
T=ST/PC
L=LC/PC
M=MU/PC
E=E2000/PC
A=FC/APC
B=SC/APC
C=LC/APC
D=E2000/APC
X=others

WANSHING OPTICAL CO., LTD
3F No.53, Sec 2, Jhonghua Rd., Sinjhuang City,
Taipei County 24246, TAIWAN, R.O.C.
HOMEPAGE: http: www.wanshing.com.tw e-mail: info@wanshing.com.tw