Polarization Maintaining Circulator

Features

- High Isolation
- Low Insertion
- Comply with RoHS

Applications

- Telecommunications
- FTTH, CATV, LAN

SPECIFICATIONS

PARAMETERS	P Grade
Operating Wavelength	1310nm or 1550nm or 1590nm
Bandwidth	±30nm
Isolation (Typical)	≧40dB(48)
Insertion Loss (Typical)	≦0.9dB(0.6)
Return Loss	≧50dB
Min. Extinction Ratio	≧22dB
Min. Cross Talk	≧50dB
Operating Temperature	-5~70 ℃
Storage Temperature	-40~85℃
Max. Power	300mW

W S C L 1 ☐ ☐ ☐ ☐ 5 0 ☐ ☐ ☐

Product Type
1=3 Port

Wavelength
1=1310nm
2=1550nm
3=1590nm
X=others

Grade
P=P Grade
X=others

Fiber Type
0=0.25mm
1=0.9mm
X=others

Fiber Length
1=1m
2=2m
3=3m
.....
X=others

Dimensions (mm)
5=5.5*35
X=others

Port 1~3 Connector
0=None
F=FC/PC
S=SC/PC
A=FC/APC
B=SC/APC
X=others

WANSHING OPTICAL CO., LTD
3F No.53, Sec 2, Jhonghua Rd., Sinjhuang City,
Taipei County 24246, TAIWAN, R.O.C.
HOMEPAGE: http: www.wanshing.com.tw e-mail: info@wanshing.com.tw