1450nm Polarization Maintaining Beam Combiner/Splitter

Features

- High Extinction
- Low Insertion Loss
- Comply with RoHS

•Applications

- EDFA
- Raman Amplifier

1450nm PM Beam Splitter SPECIFICATIONS

PARAMETERS	P Grade
Type	1x2
Operating Wavelength	1450nm
Bandwidth	±30nm
Max. Excess Loss (Typical)	≦0.65dB
Direction of Incident Polarization	Slow Axis
Min. Extinction Ratio	≧20dB
Return Loss (In/Out)	≧50dB
Operating Temperature	-5~70℃
Storage Temperature	-40~85℃
Max. Power	750mW
Dimensions	5.5mm*35mm

W S C P 4 0 1 ☐ ☐ ☐ ☐ D ☐ ☐

Wavelength
4=1450nm
X=others

Grade
0=P Grade
1=High Power 750mW
2=High Power 2W
X=others

Dimensions (mm)
0=5.5*34
1=5.5*35
2=5.5*39
3=5.5*32
X=others

Port 1,2 Fiber Type
0=0.25mm Panda Fiber
1=0.4mm Panda Fiber
2=0.9mm Panda Fiber
X=others

Port 3 Fiber Type
0=0.25mm SMF-28
1=0.9mm SMF-28
2=0.25mm Panda Fiber
3=0.9mm Panda Fiber
X=others

Fiber Length
1=1m
2=2m
3=3m
.....
X=others

Port 1,2 Connector Type
0=None
F=FC/PC
S=SC/PC
A=FC/APC
B=SC/APC
X=others

Port 3 Connector Type
0=None
F=FC/PC
S=SC/PC
A=FC/APC
B=SC/APC
X=others

WANSHING OPTICAL CO., LTD
3F No.53, Sec 2, Jhonghua Rd., Sinjhuang City,
Taipei County 24246, TAIWAN, R.O.C.
HOMEPAGE: http: www.wanshing.com.tw e-mail: info@wanshing.com.tw