SM 1W Power Handling 980nm In-Line Polarization Insensitive Isolator

Features

- High Isolation
- Low Insertion

Applications

- Telecommunications
- FTTH, CATV, LAN

SM 980nm Isolator SPECIFICATIONS

PARAMETERS	Single Stage P Grade
Operating Wavelength	980nm
Bandwidth	±10nm
Min. Isolation (Peak)	≧25dB(42)
Insertion Loss (Typical)	≦1.0dB(0.6)
Return Loss (In/Out)	≧50/50dB
PDL	≦0.1dB
Operating Temperature	-5~60℃
Storage Temperature	-40~85℃
Max. Power	1000mW
Fiber Type	HI 1060

W S C 1 1 0 1 F

Product Type
1=Single Stage

Wavelength
F=980nm
X=others

Grade
P=P Grade
X=others

Fiber Type
0=0.25mm
1=0.9mm
X=others

Fiber Length
1=1m
2=2m
3=3m
.....
X=others

Dimensions (mm)
C=68*32*32
X=others

Input Connector
0=None
F=FC/PC
S=SC/PC
T=ST/PC
L=LC/PC
M=MU/PC
E=E2000/PC
A=FC/APC
B=SC/APC
C=LC/APC
D=E2000/APC
X=others

Output Connector
0=None
F=FC/PC
S=SC/PC
T=ST/PC
L=LC/PC
M=MU/PC
E=E2000/PC
A=FC/APC
B=SC/APC
C=LC/APC
D=E2000/APC
X=others

WANSHING OPTICAL CO., LTD
3F No.53, Sec 2, Jhonghua Rd., Sinjhuang City,
Taipei County 24246, TAIWAN, R.O.C.
HOMEPAGE: http: www.wanshing.com.tw e-mail: info@wanshing.com.tw