Single Mode 980nm, 1030nm and 1064nm Coupler



Features

- Low insertion loss
- Comply with RoHS
- Comply with Telcordia GR-1209, GR-1221

Applications

- Telecommunications
- FTTH, CATV, LAN

1x2 980nm, 1030nm and 1064nm Coupler SPECIFICATIONS

PARAMETERS	P Grade
Operating Wavelength (nm)	980, 1030 or 1064±10
Max. Insertion Loss (Typical)	≦3.6dB (3.3)
Max. Uniformity (Typical)	≦0.8dB (0.4)
Return Loss/Directivity	≧50/55dB
Polarization Dependent Loss (Typical)	≦0.2dB (0.1)
Fiber Type	HI 1060 Flexcore
Storage Temperature	-40~85°C

W S C 4 1 ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐

Type
1=SWBC
X=others

Port No.
1=1x2
2=2x2
X=others

Coupling Ratio
1=50/50
2=40/60
3=30/70
4=20/80
5=10/90
6=5/95
7=3/97
8=2/98
9=1/99
A=15/85
B=25/75
C=35/65
D=45/55
X=others

Bandwidth
1=±10nm
X=others

Wavelength
9=980nm
A=1064nm
E=1030nm
X=others

Grade
1=P
X=others

Package Dimension
3=3.0*40mm
4=3.0*45mm
6=3.0*54mm
7=3.0*60mm
C=98*14*8.5mm
D=3.5*70mm
X=others

Fiber Type
1=0.25mm
2=0.9mm
3=3mm
X=others

Fiber Length
1=1m
2=2m
3=3m
4=4m
5=5m
.....
X=others

Connector Type
0=None
F=FC/PC
S=SC/PC
T=ST/PC
L=LC/PC
M=MU/PC
E=E2000/PC
A=FC/APC
B=SC/APC
C=LC/APC
D=E2000/APC
X=others

WANSHING OPTICAL CO., LTD
3F No.53, Sec 2, Jhonghua Rd., Sinjhuang City,
Taipei County 24246, TAIWAN, R.O.C.
HOMEPAGE: http: www.wanshing.com.tw e-mail: info@wanshing.com.tw