SM Plug Type Fixed Attenuator

Features

- Low Back Reflection
- Comply with RoHS
- Precise Control of Attenuation Range

Applications

- Telecommunications
- FTTH, CATV , LAN

SPECIFICATIONS

PARAMETERS	FC, SC, ST, LC, MU
Operating Wavelength (nm)	1310, 1550, 1310/1550 or 1250~1650nm
Attenuation	1~9dB ± 0.5dB
	10, 12, 15dB ± 1dB
	20, 25, 30dB ± 2dB
UPC Type Return Loss	≧50dB
APC Type Return Loss	≧65dB
Operating Temperature	-40~85°C

W S C W A [ ] [ ] 0 [ ] 0 [ ]

Attenuation Ratio

01=1dB
03=3dB
05=5dB
10=10dB
15=15dB
20=20dB
.....
X=others

Wavelength

1=1310nm
2=1550nm
3=1310/1550
4=1250~1650nm
X=others

Connector Type

F=FC/UPC
S=SC/UPC
T=ST/UPC
L=LC/UPC
M=MU/UPC
A=FC/APC
B=SC/APC
X=others

WANSHING OPTICAL CO., LTD
3F No.53, Sec 2, Jhonghua Rd., Sinjhuang City,
Taipei County 24246, TAIWAN, R.O.C.
HOMEPAGE: http: www.wanshing.com.tw e-mail: info@wanshing.com.tw