1064nm Polarization Maintaining Circulator

Features

- High Isolation
- Low Insertion
- Comply with RoHS

Applications

- Telecommunications
- FTTH, CATV, LAN

SPECIFICATIONS

PARAMETERS	P Grade	A Grade
Operating Wavelength	1064nm	
Bandwidth	±5nm	
Isolation (Typical)	≧25dB(35)	≧20dB(30)
Insertion Loss (Typical)	≦2.1dB(1.5)	≦2.8dB(2.2)
Return Loss	≧50dB	≧50dB
Min. Extinction Ratio (Typical)	≧20dB(23)	≧20dB
Min. Cross Talk	≧50dB	
Operating Temperature	-5~60 ℃	
Storage Temperature	-40~85℃	
Max. Power	300mW	

W S C L 1 4 ☐ ☐ ☐ 5 0 ☐ ☐ ☐

Product Type
1=3 Port

Wavelength
4=1064nm
X=others

Grade
P=P Grade
A=A Grade
X=others

Fiber Type
0=0.25mm
1=0.9mm
X=others

Fiber Length
1=1m
2=2m
3=3m
.....
X=others

Dimensions (mm)
5=5.5*35
X=others

Port 1~3 Connector
0=None
F=FC/PC
S=SC/PC
A=FC/APC
B=SC/APC
X=others

WANSHING OPTICAL CO., LTD
3F No.53, Sec 2, Jhonghua Rd., Sinjhuang City,
Taipei County 24246, TAIWAN, R.O.C.
HOMEPAGE: http: www.wanshing.com.tw e-mail: info@wanshing.com.tw