Polarization Maintaining In-Line Polarizer

Features

- High Extinction Ratio
- Low Insertion
- Comply with RoHS

Applications

- High Speed Communication
- Test Instrumentation

PM In-Line Polarizer SPECIFICATIONS

PARAMETERS	P Grade
Operating Wavelength	1310nm or 1480 or1550nm
Bandwidth	±50nm
Max. Excess Loss (Typical)	≦0.5dB (0.3)
Min. Extinction Ratio (Typical)	≧28dB (>30)
Return Loss (In/Out)	≧50dB
Operating Temperature	-5~70℃
Storage Temperature	-40~85℃
Max. Power	500mW
Dimensions	5.5mm*35mm

W S C Q ☐ 0 0 ☐ ☐ ☐ ☐ 0 ☐ ☐

Wavelength
1=1310nm
2=1480nm
3=1550nm
X=others

Dimensions (mm)
0=5.5*34
1=5.5*35
2=5.5*39
3=5.5*32
X=others

Port 1 Fiber Type
0=0.25mm SMF-28
1=0.9mm SMF-28
2=0.25mm Panda Fiber
3=0.4mm Panda Fiber
4=0.9mm Panda Fiber
X=others

Port 2 Fiber Type
0=0.25mm SMF-28
1=0.9mm SMF-28
2=0.25mm Panda Fiber
3=0.4mm Panda Fiber
4=0.9mm Panda Fiber
X=others

Fiber Length
1=1m
2=2m
3=3m
.....
X=others

Port 1 Connector Type
0=None
F=FC/PC
S=SC/PC
A=FC/APC
B=SC/APC
X=others

Port 2 Connector Type
0=None
F=FC/PC
S=SC/PC
A=FC/APC
B=SC/APC
X=others

WANSHING OPTICAL CO., LTD
3F No.53, Sec 2, Jhonghua Rd., Sinjhuang City,
Taipei County 24246, TAIWAN, R.O.C.
HOMEPAGE: http: www.wanshing.com.tw e-mail: info@wanshing.com.tw